

MRP-5000 FUNCTIONAL ROLL GAGES FOR TAPERED THREADS



The MRP-5000 series of thread pitch diameter gages use hardened and ground thread rolls to inspect functional size of tapered threaded connectors. The MRP-5000 gages are adjustable within a size range and have interchangeable thread rolls for inspection of all API thread forms. The gages must be preset to size using one of a variety of setting methods available. Refer to the setting options that follow. *Please specify preferred taper arms when ordering.* **Thread rolls are sold separately**.

Model	Description	Resolution	Range
MRP-501*	External Sizes by Taper, Single Taper Gage*	.0001"	1" - 21/4"
MRP-502*	Internal Sizes by Taper, Single Taper Gage*	.0001"	1" - 21/4"
MRP-5001	Internal/External Tubing and Casing Connectors	.0005"	23/8" - 51/2"
MRP-5002	Internal/External Tubing and Casing Connectors	.0005"	2%" - 13%"
MRP-5003	Internal/External Tubing and Casing Connectors	.0005"	13%" - 20"
MRP-5004	Internal/External Tubing and Casing Connectors and Internal Tool Joints	.0001"	23/8" - 95/8"

^{*}Please specify taper when ordering. Built to one specific taper. One taper per gage. Set of thread rolls included.

REPLACEMENT PARTS

Model	Description*
MRP5-10	Positioning Springs (Set of 2)
MRP5-11	Retainer Washers (Set of 2)
MRP5-12	Lock Screws (Set of 2)
MRP5-75T	3/4" TPF Taper Arms (Set of 2)
MRP5-10T	1" TPF Taper Arms (Set of 2)
MRP5-125T	11/4" TPF Taper Arms (Set of 2)
MRP5-15T	1½" TPF Taper Arms (Set of 2)
MRP5-20T	2" TPF Taper Arms (Set of 2)
MRP5-30T	3" TPF Taper Arms (Set of 2)

^{*}Taper arm price does not include thread rolls. To determine the thread rolls required, refer to thread roll chart below.

MRP-5000 THREAD ROLLS

The product thread form determines the thread roll set that will be used. Thread roll sets consist of 2 rolls supplied in a labeled storage tube.

Model	Description	
TR-8R	All API 8 Round Tubing	
TR-10R	All API 10 Round Tubing	
TR-8LP	8V API Line Pipe, American Standard NPT	
TR-11LP	11½" V API Line Pipe, American Standard NPT	
TR-B10I	API Buttress Casing, Internal, 16" - 20"	
TR-B10E	API Buttress Casing, External, 16" - 20"	
TR-B75I	API Buttress Casing, Internal, 4½" - 13¾"	
TR-B75E	API Buttress Casing, External, 4½" - 13%"	
TR-41576	P.A.C. Connections, 2 ³ / ₈ " - 3 ¹ / ₂ ", 2 ³ / ₈ " - 4" American Open Hole	
TR-4238	4", 5½", & 65%" API Full Hole 2½" - 5" Hughes Xtra Hole 2¾" - 4½" Hughes Slim Hole 3½" & 4½" API EXT Flush 2%" - 65%" API INT Flush API Numbered Connections #23 - #50 3½" - 5½" Double Streamline 65%" API REG	
TR-4338	5½", 75%", 85%" API REG , API Numbered Connections #56 - #77	
TR-5340	2%" - 4½" API REG, 3½", 4½" API Full Hole	
TR-6232	2% & 2% External Flush	
TR-61555	API Numbered Connections #10, #12, #13, #16 M.T. (Macaroni Tubing)	
TR-352H9	3 ½" - 65⁄8" Hughes H-90	
TR-353H9	7" - 85%" Hughes H-90	
TR-312SLH9	23/6" - 31/2" Hughes Slim Line	
TR-BL	Blank thread roll set	

MRP-5500 FUNCTIONAL ROLL GAGES FOR TAPERED THREADS



The MRP-5500 gage is for rotary shouldered connections. The MRP-5000 series of thread pitch diameter gages use hardened and ground thread rolls to inspect functional size of tapered threaded connectors. The MRP-5000 gages are adjustable within a size range and have interchangeable thread rolls for inspection of all API thread forms. The gages must be preset to size using one of a variety of setting methods available. Refer to the setting options that follow. Please specify preferred taper arms when ordering. Thread rolls are sold separately.

Model	Description	Resolution	Range
MRP-5501	External Tool Joints	.0001"	23/8" - 51/2"
MRP-5502	External Tool Joints	.0001"	5½" - 75/8"
MRP-5503	External Tool Joints	.0001"	85/8"
MRP-5012	Internal Tunneling Drill Pipe	.0001"	3/4" - 2"
MRP-5512	External Tunneling Drill Pipe (Please specify taper when ordering. Built to one specifc taper. One taper per gage.)	.0001"	3/4" - 2"

REPLACEMENT PARTS

Model	Description*
MRP55-125T	11/4" TPF Taper Arms (Set of 2)
MRP55-15T	1½" TPF Taper Arms (Set of 2)
MRP55-20T	2" TPF Taper Arms (Set of 2)
MRP55-30T	3" TPF Taper Arms (Set of 2)

^{*}Taper arm price does not include thread rolls. To determine the thread rolls required, refer to thread roll chart below.

MRP-5500 THREAD ROLLS

The product thread form determines the thread roll set that will be used. Thread roll sets consist of 2 rolls supplied in a labeled storage tube.

Model	Description	
TR-41576	P.A.C. Connections, 23/6" - 31/2", 23/6" - 41/2" American Open Hole	
TR-4238	4", 5½", & 65%" API Full Hole 2½" - 5" Hughes Xtra Hole 2¾" - 4½" Hughes Slim Hole 3½" & 4½" API EXT Flush 2% API Numbered Connections #23 - #50 3½" - 5½" Double Streamline 65%" API REG	
TR-4338	5½", 75%", 85%" API REG, API Numbered Connections #56 - #77	
TR-5340	2%" - 4½" API REG, 3½" & 4½" API Full Hole	
TR-6232	2%" & 21/6" External Flush	
TR-61555	API Numbered Connections #10, #12, #13, #16 M.T. (Macaroni Tubing)	
TR-352H9	3 ½" - 6%" Hughes H-90	
TR-353H9	7" - 85%" Hughes H-90	
TR-312SLH9	2%" - 3½" Hughes Slim Line	
TR-BL	Blank thread roll set	



